



# VP2130b

21.3" THINEDGE™ ULTRA-SLIM BEZEL LCD DISPLAY WITH  
8MS CLEARMOTIV™ HD BROADCAST-QUALITY VIDEO



<b>LCD</b>	Type	21.3" color TFT active matrix UXGA LCD
	Display Area	17.0" (horizontal) x 12.8" (vertical); 21.3" diagonal
	Optimum Resolution	1600x1200
	Contrast Ratio	1000:1 (typ)
	Viewing Angles	178° horizontal, 178° vertical @ contrast ratio > 10:1
	Response Time	8ms gray-to-gray (avg); 16ms black-white-black (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analog/Digital	RGB analog (75 ohms, 0.7/1.0 Vp-p)/DVI (TMDS, 100 ohms)
	Frequency	F <sub>H</sub> : 24~92kHz, F <sub>V</sub> : 50~85Hz
	Sync	H/V separated (TTL), composite sync on green
<b>COMPATIBILITY</b>	PC	VGA up to 1600x1200 non-interlaced
	Mac***	Power Mac™ G3/G4/G5 up to 1600x1200; PerfectSuite™ and pivot function not support by ViewSonic
<b>CONNECTOR</b>	Analog/Digital	15-pin mini D-sub/DVI-D (digital or analog capable)
	USB	1-up/4-down USB 2.0 hub
	Power	Internal power; 3-pin AC plug
<b>POWER</b>	Voltage	AC 100~240V, 50/60Hz (auto switch)
	Consumption	53W (typ)
<b>CONTROLS</b>	Basic	Power, 2, up, down, 1
	OnView®	Auto image adjust, contrast, brightness, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 7500K, 6500K, 5400K, 5000K, user color - RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (PIP, PIP position, PIP swap, H. size, H. position, V. position, fine tune, sharpness, scaling), setup menu (language, resolution notice, OSD position, input priority, OSD timeout, OSD background, OSD pivot), memory recall
<b>OPERATING CONDITIONS</b>	Temperature	32~104°F (0~40°C)
	Humidity	10~90% (no condensing)
<b>DIMENSIONS (W x H x D)</b>	Physical (mm)	468mm x 409mm x 315mm
	Physical (in.)	18.4" x 16.1" x 12.4"
<b>WEIGHT</b>	Net	20.3 lb. (9.2 kg)
	Gross	26.9 lb. (12.2 kg)
<b>REGULATIONS</b>		UL, cUL, FCC-B (ICES), CB, CE, TCO '99, ICES-003B, ISO13406-2, TUV/GS, TUV ERGO (covers ISO13406-2 and MPR II), TUV-S, NOM, GOST-R, HYGIENIC, ENERGY STAR®, CCC, BSMI, PSB, C-TICK, KTL/MIC, SASO, WEEE, RoHS
<b>POWER MANAGEMENT</b>		Meets TCO'99 and ENERGY STAR® standards
<b>PACKAGE CONTENTS</b>		LCD display, power cable, 15-pin VGA video cable, DVI cable, USB cable, Quick Start Guide, ViewSonic Wizard CD, PerfectSuite™ CD
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight



ISO 9001:2000  
FM 40187



ISO 14001:1996  
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

**ViewSonic®** 

*the choice of professionals*

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789  
Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

\*\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. [12620-00B-09/05] VP2130b-1

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)