

Infinite images made possible.

Expand your view with the VP2330wb 23" widescreen LCD display. This elegant display's widescreen aspect ratio ENHANCES YOUR PRODUCTIVITY, allowing you to view two complete documents or work in two applications side-by-side. Organize graphics toolbars and schematics while working in the main document and expand your notebook's display area with the VP2330wb. Built on our tradition of award-winning displays, the VP2330wb features innovative PERFECTSUITE™ SCREEN CONTROL SOFTWARE FOR THE BEST POSSIBLE FRONT-OF-SCREEN PERFORMANCE. Demanding users will revel in the advanced ergonomics including the progressive THINEDGE™ DESIGN WITH COMPREHENSIVE HEIGHT AND PIVOT* adjustments. Professional-caliber features like ClearMotiv™ 8ms gray-to-gray broadcast quality video response deliver superior clarity and perfect focus when viewing moving images making the VP2330wb the perfect choice for maximizing your visual experience.

VP2330wb

23" ULTRA-SLIM BEZEL WIDESCREEN LCD DISPLAY

WITH 8MS CLEARMOTIV™ HD
BROADCAST-QUALITY VIDEO



WIDESCREEN EXPANDS YOUR VIEW

- > **ClearMotiv 8ms video response time**
Ultra-fast 8ms gray-to-gray video response enables digital HD broadcast-quality full motion video.
- > **ThinEdge maximizes your productivity**
The ultra-slim 0.85" bezel design enhances your visual experience with clean, minimalist borders around the active image area. Suitable for tiling and stacking.
- > **Ideal for multiple-monitor setups**
ThinEdge minimizes bezel gaps between panels for a virtually continuous viewing area in multiple-panel setups.
- > **Pivot, height and wall-mount versatility**
VESA® wall-mount interface and detachable base for ergonomic flexibility with pivot*, height, tilt and 270° swivel adjustments.
- > **PerfectSuite™**
Professional-grade LCD control software featuring color calibration, asset management, theft deterrence, and auto screen rotation*.
- > **High brightness and contrast**
250-nit brightness (typ) and 800:1 contrast ratio (typ).
- > **Full 23" viewable widescreen**
- > **1920x1200 optimum resolution and HDTV-720p compatible**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

*PerfectSuite™ and pivot function not supported by ViewSonic on Apple computers.

ViewSonic 

the choice of professionals

VP2330wb

23" ULTRA-SLIM BEZEL WIDESCREEN LCD DISPLAY
WITH 8MS CLEARMOTIV™ HD BROADCAST-QUALITY VIDEO



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

**Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12716-00B-11/05] VP2330wb-1

LCD	Type	23" color TFT active matrix WUXGA LCD
	Display Area	19.5" horizontal x 12.2" vertical; 23.0" diagonal
	Optimum Resolution	1920x1200
	Contrast Ratio	800:1 (typ)
	Viewing Angles	170° horizontal, 170° vertical @ contrast ratio > 10:1
	Response Time	8ms gray-to-gray (avg); 16ms black-white-black (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	250 cd/m2 (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7/1.0 Vp-p)/DVI (TMDS, 100 ohms)
	Frequency	F _H : 24~96kHz, F _V : 50~85Hz
	Sync	H/V separated (TTL), composite sync on green
COMPATIBILITY	PC	VGA up to 1920x1200 non-interlaced
	Mac [®] **	Power Mac™ G3/G4/G5 up to 1920x1200
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-I
	Power	External power adapter, 3-pin (CEE22) plug
POWER	Voltage	AC 100~240V, 50/60Hz (auto switch)
	Consumption	70W (typ)
CONTROLS	Basic	Power, 2, up, down, 1
	OnView [®]	Auto image adjust, contrast, brightness, input select (analog, digital), audio (volume, mute), ViewMatch [®] color adjust (sRGB, 9300K, 7500K, 6500K, 5400K, 5000K, user color - RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (PIP, hue saturation, H. size, H. position, V. position, fine tune, sharpness, scaling), setup menu (language, resolution notice, input priority, OSD position, OSD timeout, OSD background), OSD pivot, memory recall
OPERATING CONDITIONS	Temperature	32~104°F (0~40°C)
	Humidity	10~90% (non-condensing)
DIMENSIONS (W x H x D)	Physical (mm)	542mm x 539mm x 295mm
	Physical (in.)	21.3" x 21.2" x 11.6"
WEIGHT	Net	17.3 lb. (7.8 kg)
	Gross	26.4 lb. (12.0 kg)
REGULATIONS		UL, cUL, FCC-B (ICES), CB, CE, TCO'99, ICES-003B, ISO13406-2, TUV/GS, TUV ERGO (covers ISO13406-2 & MPR II), TUV-S, NOM, GOST-R, ENERGY STAR [®] , CCC, BSMI, PSB, C-TICK, KTL/MIC, SASO, WEEE, RoHS
POWER MANAGEMENT		Meets TCO'99 and ENERGY STAR [®] standards
PACKAGE CONTENTS		LCD display, power cable, AC adapter, 15-pin VGA video cable, DVI cable, USB cable, Quick Start Guide, ViewSonic Wizard CD, PerfectSuite™ CD
WARRANTY		Three-year limited warranty on parts, labor and backlight

ViewSonic[®]



the choice of professionals

For more product information, visit us on the web at ViewSonic.com