

VX2235wm

22" WIDESCREEN LCD WITH CLEARMOTIV™ 5MS BROADCAST-QUALITY VIDEO



LCD	Type	22" Wide Color TFT Active Matrix LCD
	Display Area	18.7" horizontal x 11.7" vertical; 22" diagonal
	Optimum Resolution	1680x1050
	Contrast Ratio	700:1 (typ)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	280 cd/m2 (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D (TMDS, 100 ohms)
	Frequency	F _H : 30~82kHz, F _V : 50~85Hz
	Sync	H/V separated (TTL), composite, sync-on-green
COMPATIBILITY	PC	VGA up to 1680x1050 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1680x1050
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D
	Power	3-pin AC plug (CEE22)
AUDIO	Speakers	2x2.5-watt
POWER	Voltage	AC 100~240V, 50~60Hz (auto switch)
	Consumption	48W (typ)
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 6500K-default, 5400K, user color - RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu, language, resolution notice, OSD position, OSD timeout, OSD background, memory recall
OPERATING	Temperature	41~95°F (5~35°C)
CONDITIONS	Humidity	20~80% (non-condensing)
DIMENSIONS (W x H x D)	Physical (mm)	524mm x 482mm x 244mm (with stand) 524mm x 388mm x 58mm (without stand)
	Physical (in.)	20.6" x 19" x 9.6" (with stand) 20.6" x 15.3" x 2.3" (without stand)
WEIGHT	Net	13.2 lb. (6.0 kg) (with stand)
	Gross	16.5 lb. (7.5 kg) (with stand)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, NEMKO/GS (covers TUV/GS), NEMKO ERGO (covers TUV/ERGO, ISO13406-2 & MPR II), MPR II, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, Argentina-S, Green Mark, RoHS
POWER MANAGEMENT		Meets MPR II and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty on LCD, parts and labor



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [13046-00B-06/06] VX2235wm-1

ViewSonic 

the choice of professionals

For more product information, visit us on the web at ViewSonic.com