

VA926

19" VALUE SERIES LCD
WITH 5MS VIDEO RESPONSE

Budget savvy desktop space saver.

ViewSonic's 19" VA926 LCD is a brilliant choice for upgrading your home or small office. This ultra-slim, Vista-certified LCD DELIVERS AN IMPRESSIVE ARRAY OF FEATURES that will enhance your productivity while helping you stay within your budget. With OptiSync® digital and analog inputs, 2000:1 DYNAMIC CONTRAST RATIO (typ) and fast ClearMotiv® 5ms video response, you'll enjoy crystal-clear graphics, video and text. The latest OSD/power lock and AutoTune® functions MAXIMIZE AND MAINTAIN YOUR DISPLAY SETTINGS. The VA926 displays excellent taste while enhancing your home or small office desktop.



2000:1
Dynamic Contrast Ratio

ATTRACTIVE STYLING. ATTRACTIVE PRICE.

- > Fast 5ms video response delivers superior picture clarity
- > Full 19" viewable screen
Displays a full, flat 19" viewable area with crisp detail and fully saturated color.
- > 1280x1024 native resolution
Incredible image detail for sharp text and graphics.
- > 2000:1 dynamic contrast ratio (typ)
Provides for darker black levels and better overall front-of-screen performance.
- > Stylish slim-bezel design
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > OptiSync® digital/analog inputs expand your connectivity
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > OSD/power lock secures your settings
Prevents changes to monitor settings and maintains an optimized image.
- > OnView® controls for superior screen adjustability
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Windows Vista certified
- > ViewSonic Wizard included
User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > PC and Mac® compatible
- > TCO'03 and ENERGY STAR® qualified



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VA926

19" VALUE SERIES LCD WITH 5MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13627-01B-09/07] VA926-1

LCD	Type	19" color TFT active matrix SXGA LCD
	Display Area	14.8" horizontal x 11.9" vertical; 19.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	1000:1 static (typ), 2000:1 dynamic (typ)
	Viewing Angles	170° horizontal, 160° vertical
	Response Time	5ms (typ)
	Light Source	Long life, 40,000 hrs. (typ)
VIDEO INPUT	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D
COMPATIBILITY	Frequency	F _H : 30~82kHz, F _V : 50~75Hz
	Sync	H/V separated (TTL)
CONNECTOR	PC	VGA up to 1280x1024 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1280x1024
POWER	Analog/Digital	15-pin mini D-sub/Digital
	Power	3-pin AC plug (CEE22)
CONTROLS	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
	Consumption	32W (typ)
ERGONOMICS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, contrast, brightness, input select, ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
OPERATING	Tilt	-5°/+20°
CONDITIONS	Temperature	32~104°F (0~40°C)
DIMENSIONS	Humidity	10~90% (non-condensing)
(W x H x D)	Physical with stand	16.2" x 17.1" x 7.7" (412mm x 434mm x 194mm)
	Physical without stand	16.2" x 14.0" x 2.5" (412mm x 355mm x 64mm)
WEIGHT	Net with stand	8.4 lb. (3.8 kg)
	Net without stand	7.3 lb. (3.3 kg)
	Gross with stand	11.1 lb. (5.0 kg)

REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, TUV-S, TUV/GS, TUV/ERGO (covers ISO13406-2), MPR II, BSMI, CCC, ENERGY STAR®, PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver

RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.

POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards

PACKAGE CONTENTS LCD display, video cable, power cable, Quick Start Guide, ViewSonic Wizard (DVI cable not included)

WARRANTY Three-year limited warranty on parts, labor and backlight

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com